JCVISION Technology Inc
5F, Wepark High-tech part, Pinghu, Longgang District, Shenzhen, Guangdong Province, China. 518172
Email: info@jcvision-edu.com Web: www.jcvision-edu.com

JCVision 65inch JCHub Interactive Flat Panel Display Specification - JC-T65K

Zero lamination process, low parallax writing, wider viewing angle

4mm anti-glare tempered glass

Equipped with 4K ultra-high-definition display, supporting full-channel 4K UI display

Support wireless screen transmission function

igh-precision infrared touch, smooth writing

Support dual-pen simultaneous writing and dual-color display, making multi-person collaboration easier

High-level welcome application, rich on-site interactive experience, very interesting

Multi-window heavy debut, parallel tasks, wider scenes

New floating ball mode, quick customization of functions, use at will

Eye protection, lock screen, touch lock and other small tools

Support multi-user function

Support palm protection

Specifications

Display	size	65inch
	Response time	8 ms
	Aspect Ratio	16:9
	Maximum display size	1429(H)×804(V)mm
	Resolution	3840 (H) × 2160 (V)
	Pixel pitch	0.372×0.372mm
	Refresh rate	60Hz
	Color	1.07B (10bit)
	Color gamut NTSC (Typ)	72%
	Contrast(Typ)	1200:1
	Viewing Angle	178°(H/V)
	Backlight type	DLED
	Screen brightness (Typ)	350cd/m2
	life	≥30000 hours
Speaker	Channel	2
	power	2×15W
	Optional	*2.1 chanel:2×15W+1×20W*
Touch Input & Writing	Identification principle	Infrared recognition
	Support system	Windows10/Windows8/Windows7/Windows XP/Android/Linux/Mac OS X/Chrome
	Touch points	20 Touch Points
	Minimum Identifiable Object	2mm
	Input method	Finger, passive infrared pen
	Response time	≤5ms
	Touch accuracy	±1mm

	Writing height	≤3mm
	Writing display	Single pen two colors
	Output coordinates	32767 (W) ×32767 (D)
Android OS	Chip Solution	RK3576
	System version	Android 16 .0
	Frequency	2.2GHZ
	CPU	Quad-core A72*4+A53*4
	GPU	G52MC3
	RAM	8GB/16GB
	ROM	64GB/128GB/256GB
	OSD	English, Simplified Chinese, and other language
Bluetooth	Version	5.2
	Operating frequency	2.4GHz & 5GHz
	Working distance	0~10m
	illustrate	Built-in Bluetooth
Wifi	Version	802.11ac/b/g/n/a/ax
	Operating frequency	2.4GHz/5GHz
	Working distance	0~10m
	Remark	Built-in Wifi
Front Interface	USB 3.0	3
	HDMI IN	1
	Touch USB	1
	TYPE-C	1
	power button	1
	NFC (Optional)	*1*
Back Ports (Interfaces)	RS232	1
	MIC IN	1
	SPDIF	1
	LINE OUT	1
	RJ45 IN	1
	RJ45 OUT	1
	Touch USB	1
	HDMI IN	2 (1 support ARC)
	DP in	1
	HDMI out	1
	TYPE-C	1
	USB 3.0	2
	USB 2.0	1
	TF-Card	1
Power	Power Input	100-240V～ 50/60Hz 2.8A
	Maximum power consumption of the whole machine	250W
	Standby power consumption	≤0.5W
Dimensions	Overall dimensions (length x width x thickness)	1485*887*120mm
	Packing size (length x thickness x height)	1600*1000*200mm
	Thickness of whole machine + wall mount	143mm
	VESA hole specifications (length x width)	500×400mm
	Wall Mount Screw Specifications	M8×25mm
	net weight	35KG
	Gross Weight	42KG
Environmental	Operating temperature	0℃~40℃
	Operating humidity	10%~90%RH
	Storage temperature	-20℃~60℃
	Storage humidity	10%~90%RH

	Working height	Below 5000 meters
Accessories	Power cord	×1
	Writing pen	×2
	Wall Mount	×1
	Quick Start Guide	×1
Optional Module	OPS specifications (LxWxD)	OPS size (120mm*180mm*30mm) OPS size (195mm*180mm*30mm) OPS size (195mm*180mm*42mm)